

LB480A Pulse Profiling USB PowerSensor+™

Order Guide



Each unit ships with the following equipment:

- Selected options, both hardware and software
- Standard or optional return to factory warranty
- USB cable (2-meter length)
- Media containing software, Data Sheet, Product Manual and Programming Guide
- Quick Start Guide and Quick Start Card
- NIST traceable calibration certification
- Packing list and invoice

PowerSensor+™ Ordering Example:

Model/Opt	Description	Qty	Cost
LB480A	Pulse Profiling Wide Dynamic Range PowerSensor+™	1	\$1945
+0SF	SMA female input connector <i>(you must specify one connector option)</i>	1	\$0
+001	Recorder output	1	\$275
+004	Add filters	1	\$995
+CW3	Three year extended warranty and calibration service	1	\$700

Model No. and Options	Description	Price USD ²
LB480A	Pulse Profiling Wide Dynamic Range PowerSensor+™ (0.1 – 8 GHz)	1945
Select one connector option:		
+0SM	SMA male	0
+0SF	SMA female	0
+0TM	TNC male	65
+0TF	TNC female	65
+0NM	N male	65
+0NF	N female	65
Additional Options:		
+20M	Additional male connector ¹	95
+20F	Additional female connector ¹	95
+001	Add recorder out	275
+003	External hardware trigger in/out (standard for LB480A)	0 - included
+004	Add 100 kHz, 200 kHz, 300 kHz, 500 kHz, 1 MHz, 2 MHz, 3 MHz, 5 MHz, 10 MHz filters	995
+CW3	Three year extended warranty and calibration service	700
+W03	Three year extended warranty	150
+C03	Three year extended calibration service	600

¹ Additional connectors are provided for convenience to allow the user to switch between connector sexes. Calibration and specifications on units with user replaced connectors are not guaranteed.

² FOB Origin (LadyBug Technologies LLC, Santa Rosa, CA, USA).