

LB579A USB PowerSensor+™

Order Guide



Each unit ships with the following equipment:

- Selected options, both hardware and software
- Standard or optional return to factory warranty
- USB cable (2-meter length)
- CD containing software, Data Sheet, Product Manual and Programming Guide
- Quick Start Guide and Quick Start Card
- NIST traceable calibration certification
- Packing list and invoice

PowerSensor+™ Ordering Example:

| Model/Opt | Description | Qty | Cost |
|-----------|---|-----|--------|
| LB579A | CW Wide Dynamic Range PowerSensor+™ | 1 | \$2745 |
| +0SF | SMA female input connector (<i>you must specify one connector option</i>) | 1 | \$0 |
| +001 | Recorder output | 1 | \$275 |
| +003 | Trigger in/out | 1 | \$275 |
| +CW3 | Three year extended warranty and calibration service | 1 | \$750 |

| Model No. and Options | Description | Price USD ² |
|-------------------------------------|---|------------------------|
| LB579A | CW Wide Dynamic Range PowerSensor+™ (.01 -18 GHz) | 2745 |
| Select one connector option: | | |
| +0SM | SMA male | 0 |
| +0SF | SMA female | 0 |
| +0TM | TNC male | 65 |
| +0TF | TNC female | 65 |
| +0NM | N male | 65 |
| +0NF | N female | 65 |
| Options: | | |
| +20M | Additional male connector ¹ | 95 |
| +20F | Additional female connector ¹ | 95 |
| +001 | Add recorder out for LB579A | 275 |
| +003 | Add triggering for LB579A | 275 |
| +CW3 | Three year extended warranty and calibration service for LB579A | 750 |
| +W03 | Three year extended warranty for LB579A | 165 |
| +C03 | Three year extended calibration service for LB579A | 650 |

¹ Additional connectors are provided for convenience to allow the user to switch between connector sexes. Calibration and specifications on units with user replaced connectors are not guaranteed.

² FOB Origin (LadyBug Technologies LLC, Santa Rosa, CA, USA).