

LB579A USB PowerSensor+™

Order Guide



Each unit ships with the following equipment:

- Selected options, both hardware and software
- Standard or optional return to factory warranty
- USB cable (2-meter length)
- Media containing software, Data Sheet, Product Manual and Programming Guide
- Quick Start Guide and Quick Start Card
- NIST traceable calibration certification
- Packing list and invoice

PowerSensor+™ Ordering Example:

Model/Opt	Description	Qty	Cost
LB579A	CW Wide Dynamic Range PowerSensor+™	1	\$2470
+0SF	SMA female input connector (<i>you must specify one connector option</i>)	1	\$0
+001	Recorder output	1	\$275
+003	Trigger in/out	1	\$275
+CW3	Three year extended warranty and calibration service	1	\$750

Model No. and Options	Description	Price USD ²
LB579A	CW Wide Dynamic Range PowerSensor+™ (.01 -18 GHz)	2470
Select one connector option:		
+0SM	SMA male	0
+0SF	SMA female	0
+0TM	TNC male	65
+0TF	TNC female	65
+0NM	N male	65
+0NF	N female	65
Options:		
+20M	Additional male connector ¹	95
+20F	Additional female connector ¹	95
+001	Add recorder out for LB579A	275
+003	Add triggering for LB579A	275
+CW3	Three year extended warranty and calibration service for LB579A	750
+W03	Three year extended warranty for LB579A	165
+C03	Three year extended calibration service for LB579A	650

¹ Additional connectors are provided for convenience to allow the user to switch between connector sexes. Calibration and specifications on units with user replaced connectors are not guaranteed.

² FOB Origin (LadyBug Technologies LLC, Santa Rosa, CA, USA).