

LB679A CW & Pulse (Peak) USB PowerSensor+™

Order Guide



Each unit ships with the following equipment:

- Selected options, both hardware and software
- Standard or optional return to factory warranty
- USB cable (2-meter length)
- Media containing software, Data Sheet, Product Manual and Programming Guide
- Quick Start Guide and Quick Start Card
- NIST traceable calibration certification
- Packing list and invoice

PowerSensor+™ Ordering Example:

| Model/Opt | Description |
|-----------|---|
| LB679A | CW Wide Dynamic Range PowerSensor+™ |
| +0SF | SMA female input connector (<i>you must specify one connector option</i>) |
| +001 | Recorder output |
| +003 | Trigger in/out |
| +CW3 | Three year extended warranty and calibration service |

| Model No. and Options | Description |
|-------------------------------------|--|
| LB679A | CW Wide Dynamic Range PowerSensor+™ |
| Select one connector option: | |
| +0SM | SMA male |
| +0SF | SMA female |
| +35M | 3.5 mm male |
| +35F | 3.5 mm female |
| +0NM | N male |
| +0NF | N female |
| Additional Options: | |
| +20M | Additional male connector ¹ |
| +20F | Additional female connector ¹ |
| +001 | Add recorder out |
| +003 | Add external triggering for LB679A |
| +004 | Filter option not available for LB679A |
| +C03 | Three year extended calibration service for LB679A |

¹ Additional connectors are provided for convenience to allow the user to switch between connector sexes. Calibration and specifications on units with user replaced connectors are not guaranteed.

² FOB Origin (LadyBug Technologies LLC, Santa Rosa, CA, USA), shipping and taxes extra